NSN 5935-01-168-3970

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-168-3970 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, flush mount **Overall Length:** 1.694 inches **Overall Height:** 3.090 inches **Overall Width:** 2.015 inches **Environmental Protection:** Cold resistant and heat resistant Center To Center Distance Between Mounting Facilities Parallel To Height: 2.783 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.437 inches **Distance From Mounting Shoulder To Front Face:** 0.065 inches **Threaded Device Type:** Mounting hole **Mating End Quantity: Contact Position Arrangement Style:** C2 1st mating end **Contact Removability:** Removable 2nd mating end single contact grouping **Polarization Method:** Mating end Shell Type: Thready Qty Per Inch (tpi): 40 **Thread Size:** 0.112 inches **Terminal Location:** Back 2nd mating end single contact grouping **Contact Material:**

Copper alloy 2nd mating end single contact grouping

Contact Surface Treatment:

Gold 2nd mating end single contact grouping

NSN 5935-01-168-3970

Insert Material:

Electrical Receptacle Connector - Page 2 of 2



Plastic all mating ends
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response 2nd mating end single contact grouping
Terminal Type:
Crimp 2nd mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416 federal specification single treatment response
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.057 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.