NSN 5935-01-168-5918

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-168-5918

Body Style:
Straight shape
Overall Length:
2.729 inches
Overall Height:
0.683 inches
Overall Width:
0.494 inches
Environmental Protection:
Corrosion resistant and moisture proof and shock resistant and vibration proof and heat resistant and cold resistant
Unthreaded Mounting Hole Diameter:
Between 0.086 inches and 0.091 inches
Distance Between Mounting Facility Centers:
2.500 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
37 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end and glass fiber single mating end
Contact Surface Treatment Specification:
Mil-g-45204 type 1, grade c military specification 1st treatment response single mating end single contact grouping and mil-c-14550 military
specification 2nd treatment response single mating end single contact grouping
Criticality Code Justification:
Feat
Terminal Type:
Pin single mating end single contact grouping
Shell Material:

Steel

NSN 5935-01-168-5918

Fiig: A039b0

Mil-std (military Standard):

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416 type 2, cl 2 federal specification 1st treatment response
Insert Material Specification:
Mil-m-14 type gdi-30f or type sdg-f military specification all material responses single mating end
Included Contact Quantity:
37 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Reverse float mount for front panel mounting
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.037 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No