Electrical Receptacle Connector - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-01-168-7495

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight shape w/cable clamp
Overall Length:
1.500 inches
Bushing Diameter:
0.505 inches
Overall Height:
Between 0.680 inches and 0.700 inches
Overall Width:
Between 0.680 inches and 0.700 inches
Environmental Protection:
Moisture proof and shock proof and vibration proof
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 0.496 inches and 0.504 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 0.496 inches and 0.504 inches
Distance From Mounting Shoulder To Front Face:
Between 0.540 inches and 0.570 inches
Threaded Device Type:
Mounting hole
Mating End Quantity:
1
Contact Position Arrangement Style:
Tnc single mating end
Contact Removability:
Removable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
56
Thread Size:
0.099 inches
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping



Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Copper alloy

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material:

Gold

Test Data Document:

81349-mil-c-39012 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unf

Specification Data:

81349-mil-c-39012/29 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0