Electrical Plug Connector - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-01-169-4128

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

2.000 inches

Overall Diameter:

1.000 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

N single mating end

Contact Removability:

Removable single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling nut

Connector Cable Strain Relief Method:

Compression nut

Thready Qty Per Inch (tpi):

36

Thread Size:

0.250 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, grade c, class 2 military specification 1st treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

NSN 5935-01-169-4128 Electrical Plug Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Shell Surface Treatment Specification:
Mil-a-8625 military specification single treatment response
Shell Material Specification:
Qq-a-225/10 federal specification single material response
Insert Material Specification:
Mil-p-19468 military specification single material response single mating end
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.