Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-169-4155

| Body Style:   |
|---|
| Right angle type  |
| Overall Length:   |
| 2.407 inches  |
| Overall Height:   |
| 0.594 inches  |
| Overall Width:  |
| 0.470 inches  |
| Unthreaded Mounting Hole Diameter:  |
| 0.125 inches  |
| Distance Between Mounting Facility Centers:   |
| 2.157 inches  |
| Mating End Quantity:  |
| 1   |
| Contact Position Arrangement Style:   |
| 2 rows of independent contacts inserted board single mating end   |
| Contact Removability:   |
| Nonremovable single mating end single contact grouping  |
| Contact Maximum Current Rating In Amps:   |
| 5.0 single mating end single contact grouping   |
| Contact Maximum Dc Voltage Rating In Volts:   |
| 1800.0 single mating end single contact grouping  |
| Terminal Location:  |
| Side single mating end single contact grouping  |
| Contact Material:   |
| Copper alloy single mating end single contact grouping  |
| Contact Surface Treatment:  |
| Gold single mating end single contact grouping and nickel single mating end single contact grouping       |
| Insert Material:  |
| Plastic diallyl phthalate single mating end   |
| Contact Surface Treatment Specification:  |
| Mil-g-45204 ty ii military specification 1st treatment response single mating end single contact grouping |
| Terminal Type:  |
| Solder well single mating end single contact grouping   |
| Insert Material Specification:  |
| Mil-m-14 military specification single material response single mating end                                |
| Included Contact Quantity:  |
| 20 single mating end single contact grouping  |
| Included Contact Type:  |
| Bifurcated spring single mating end single contact grouping   |
| Precious Material And Location:   |
| Contact surfaces gold   |

Contact surfaces gold



**Precious Material And Weight:** 

0.020 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.