

View Online at <https://aerobasegroup.com/nsn/5935-01-169-6415>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

0.680 inches

**Overall Diameter:**

0.250 inches

**Cable Entrance Diameter:**

0.200 inches

**Threaded Device Type:**

Mounting bushing

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Nonstd single mating end

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

115.0 single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.190 inches

**Contact Material:**

Copper single mating end single contact grouping

**Contact Surface Treatment:**

Cadmium single mating end single contact grouping

**Contact Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response single mating end single contact grouping

**Terminal Type:**

Turret single mating end single contact grouping

**Contact Material Specification:**

Qq-b-626, comp 22, 1/2 h federal specification single material response single mating end single contact grouping

**Shell Material:**

Copper

**Shell Surface Treatment:**

Cadmium

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Shell Material Specification:**

Qq-b-626, comp 22, 1/2 h federal specification single material response

**Included Contact Quantity:**

1 single mating end single contact grouping

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0