NSN 5935-01-169-9982

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-169-9982

| Thread Class: |
|---|
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape, external/internal coupling |
| Overall Diameter: |
| 0.750 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 2 |
| Contact Position Arrangement Style: |
| Nonstd all mating ends |
| Contact Removability: |
| Nonremovable all mating ends single contact grouping |
| Polarization Method: |
| Mating end |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Bayonet pin and externally threaded shell |
| Thready Qty Per Inch (tpi): |
| 18 |
| Thread Size: |
| 0.562 inches |
| Insert Material: |
| Plastic polytetrafluoroethylene all mating ends |
| Shell Material: |
| Copper alloy |
| Shell Surface Treatment: |
| Gold and silver |
| Shell Surface Treatment Specification: |
| Mil-g-45204, ty ii, cl 2 military specification 1st treatment response and qq-s-365a, ty ii or iii federal specification 2nd treatment response |
| Shell Material Specification: |
| Qq-b-626 federal specification single material response and qq-c-530 federal specification single material response |
| Insert Material Specification: |
| Mil-p-19468 military specification single material response all mating ends |
| Included Contact Quantity: |
| 1 all mating ends single contact grouping |
| |

Included Contact Type:

Coaxial socket all mating ends single contact grouping

NSN 5935-01-169-9982

Connector Adapter - Page 2 of 2



| Precious Material And Location: |
|---|
| Shell surfaces gold and shell surfaces silver |
| Precious Material: |
| Gold and silver |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| |

A039b0

Mil-std (military Standard):

Mil-p-19468 spec.