## NSN 5935-01-170-5720



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-170-5720 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.484 inches **Overall Height:** 1.281 inches **Overall Width:** 1.281 inches **Environmental Protection:** Corrosion resistant and moisture resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.969 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.969 inches **Distance From Mounting Shoulder To Front Face:** 0.562 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 16s-8 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0

Shell Type:

Solid

## NSN 5935-01-170-5720

Electrical Receptacle Connector - Page 2 of 2



| Connector Locking Method:                              |
|--|
| Externally threaded shell                              |
| Thready Qty Per Inch (tpi):                            |
| 20   |
| Thread Size:   |
| 1.000 inches   |
| Terminal Location:                                     |
| Back single mating end single contact grouping         |
| Contact Material:                                      |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment:                             |
| Gold single mating end single contact grouping         |
| Insert Material:                                       |
| Rubber single mating end                               |
| Terminal Type:   |
| Solder well single mating end single contact grouping  |
| Shell Material:  |
| Aluminum alloy   |
| Shell Surface Treatment:                               |
| Cadmium  |
| Included Contact Quantity:                             |
| 5 single mating end single contact grouping            |
| Included Contact Type:                                 |
| Round socket single mating end single contact grouping |
| Precious Material And Location:                        |
| Contact surfaces gold                                  |
| Precious Material And Weight:                          |
| 0.005 gold grains, troy                                |
| Precious Material:                                     |
| Gold   |
| Thread Series Designator:                              |
| Unef   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:                                       |
|  |
| Demilitarization:                                      |
| No   |
| Fiig:  |
| A039b0   |