Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-170-9123

| Thread Class: |
|--|
| 2a |
| Thread Direction: |
| Right-hand |
| Overall Length: |
| 1.330 inches |
| Environmental Protection: |
| Waterproof |
| Unthreaded Mounting Hole Diameter: |
| 0.096 inches |
| Distance Between Mounting Facility Centers: |
| 1.125 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| N single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Externally threaded shell |
| Thready Qty Per Inch (tpi): |
| 24 |
| Thread Size: |
| 0.625 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Surface Treatment: |
| Silver single mating end single contact grouping |
| Contact Surface Treatment Specification: |
| Qq-s-365 federal specification single treatment response single mating end single contact grouping |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Shell Material: |
| Copper alloy |
| Shell Surface Treatment: |
| Silver |
| Included Contact Quantity: |
| 1 single mating end single contact grouping |
| |



Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact and shell surfaces silver

Precious Material And Weight:

0.105 silver grains, troy

Precious Material:

Silver

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0