

View Online at <https://aerobasegroup.com/nsn/5935-01-171-1846>

Thread Class:

2a and 2a and 2a

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.860 inches

Overall Diameter:

0.750 inches

Environmental Protection:

Shock proof and vibration proof

Distance From Mounting Shoulder To Front Face:

Between 0.796 inches and 0.843 inches

Mounting Facility Thickness:

0.310 inches

Threaded Device Type:

Coupling facility and mounting bushing

Mating End Quantity:

2

Contact Position Arrangement Style:

Tnc 1st mating end

Contact Removability:

Removable all mating ends all contact groupings

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends all contact groupings

Thready Qty Per Inch (tpi):

24 and 28 and 24

Thread Size:

0.625 inches and 0.438 inches and 0.625 inches

Contact Surface Treatment:

Gold all mating ends all contact groupings

Contact Surface Treatment Specification:

Mil-g-45204 type 2, cl 2 military specification single treatment response all mating ends all contact groupings

Shell Material:

Copper alloy

Included Contact Quantity:

1 2nd mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/double flat

Included Contact Type:

Coaxial socket all mating ends all contact groupings

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef and unef and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.