Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-171-1850

#### **Body Style:**

Straight type

**Overall Length:** 

6.400 inches

#### **Overall Height:**

1.090 inches

#### **Overall Width:**

0.350 inches

#### **Environmental Protection:**

Vibration resistant and shock resistant and salt water resistant and humidity resistant and thermal shock resistant

#### **Unthreaded Mounting Hole Diameter:**

0.120 inches

#### **Distance Between Mounting Facility Centers:**

6.150 inches

#### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

3 rows of contacts non-inserted board single mating end

#### Contact Removability:

Nonremovable single mating end single contact grouping

#### **Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

# **Polarization Method:**

Guide pin/socket

#### **Connector Locking Method:**

Friction

#### **Operating Tempurature Rating:**

Between -65.0 degrees celsius and 125.0 degrees celsius

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

# Insert Material:

Plastic polyphenylene single mating end

# Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

# **Terminal Type:**

Wire wrap single mating end single contact grouping

# **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping

# NSN 5935-01-171-1850

Electrical Receptacle Connector - Page 2 of 2



# **Guide Design And Location:** D shape pin left-hand at 12 oclock and d shape socket right-hand at 12 oclock **Insert Material Specification:** Mil-m-24519 military specification single material response single mating end **Included Contact Quantity:** 160 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.160 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.