## NSN 5935-01-171-5715

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-171-5715

view Online at https://defobasegroup.com/hsh/5555-01-171-5715
Body Style:
Straight shape spring mount
Overall Length:
1.641 inches
Overall Diameter:
2.104 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration proof
Mating End Quantity:
1
Contact Position Arrangement Style:
37p single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
25.0
Shell Type:
Solid
Connector Locking Method:
Spring friction
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Contact Surface Treatment Specification:
Mil-g-45204, type 1, cl 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290,
grade e federal specification 2nd treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
37 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping

Contact surfaces gold

**Precious Material And Weight:** 

**Precious Material And Location:** 

0.037 gold grains, troy

## NSN 5935-01-171-5715

Electrical Receptacle Connector - Page 2 of 2



Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-g-45204 spec.