NSN 5935-01-172-4289

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-172-4289

Body Style:
Straight type
Overall Length:
7.800 inches
Overall Width:
0.285 inches
Body Height:
0.580 inches
Environmental Protection:
Humidity resistant and moisture resistant and thermal shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.073 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic polyamide single mating end
Contact Surface Treatment Specification:
Mil-g-45204, ty ii military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification
2nd treatment response single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Contact Material Specification:
Qq-b-613, comp 2 federal specification single material response single mating end single contact grouping

Guide Design And Location:

D shape pin left-hand at 3 oclock and d shape pin right-hand at 3 oclock

Insert Material Specification:

Mil-m-20693 military specification single material response single mating end

NSN 5935-01-172-4289

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:

110 single mating end single contact grouping

Included Contact Type:

Flat pin single mating end single contact grouping

Special Features:

Four mounting holes, two on each end

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.110 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.