Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-172-9847

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
2.088 inches
Overall Height:
0.663 inches
Overall Width:
0.494 inches
Environmental Protection:
Vibration resistant
Distance Between Mounting Facility Centers:
1.852 inches
Threaded Device Type:
Mounting hole
Mating End Quantity:
1
Contact Position Arrangement Style:
25 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Friction
Thready Qty Per Inch (tpi):
40
Thread Size:
0.112 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

NSN 5935-01-172-9847

Electrical Receptacle Connector - Page 2 of 2



Insert Material:	
	ate single mating end
	eatment Specification:
	specification 1st treatment response single mating end single contact grouping
Terminal Type:	
	ating end single contact grouping
Shell Material:	
Steel	
Shell Surface Treat	
Cadmium and chron	
Insert Material Spe	
	military specification single material response single mating end or mil-m-14, ty sdg-f military specification single material
response single mat	
Included Contact C	
	d single contact grouping
Included Contact T	
	mating end single contact grouping
Special Features:	
Furnished items - m	
Precious Material	
Contact surfaces go	
Precious Material	
0.025 gold grains, t	roy
Precious Material:	
Gold	
Thread Series Desi	gnator:
Unc	
Shelf Life:	
N/a	
Unit Of Measure:	
 Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military Sta	andard):
Mil-g-45204 spec.	