NSN 5935-01-173-7316

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-173-7316 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.290 inches **Overall Height:** 1.562 inches **Overall Width:** 1.562 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof **Unthreaded Mounting Hole Diameter:** 0.128 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 1.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.250 inches **Distance From Mounting Shoulder To Front Face:** Between 0.815 inches and 0.820 inches **Threaded Device Type:** Back shell **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 21-11 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Thread Length:** 0.219 inches

18

Thready Qty Per Inch (tpi):

NSN 5935-01-173-7316

Electrical Receptacle Connector - Page 2 of 2



| Thread Size: |
|--|
| 1.188 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Contact Surface Treatment Specification: |
| Mil-g-45204 military specification single treatment response single mating end single contact grouping |
| Terminal Type: |
| Crimp single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Nickel |
| Shell Surface Treatment Specification: |
| Mil-c-26074 military specification single treatment response |
| Included Contact Quantity: |
| 11 single mating end single contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.011 gold grains, troy |
| Precious Material: |
| Gold |
| Test Data Document: |
| 81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Thread Series Designator: |
| Unef |
| Specification Data: |
| 96906-ms27656 government standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| |

Mil-std (military Standard):

No Fiig: A039b0