NSN 5935-01-174-1133

Thread Class:

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-174-1133

2a and 2b and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape
Overall Length:
2.850 inches
Overall Height:
0.723 inches
Overall Width:
0.250 inches
Environmental Protection:
Cold resistant and heat resistant
Distance Between Mounting Facility Centers:
2.650 inches
Threaded Device Type:
Coupling facility and mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Connector Locking Method:
Jackscrew-socket
Thready Qty Per Inch (tpi):
56 and 56 and 56
Thread Size:
0.086 inches and 0.086 inches and 0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic polyphenylene single mating end

NSN 5935-01-174-1133

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Criticality Code Justification:

Feat

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-24519 military specification single material response single mating end

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

49 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

0.060 in. Diameter polarizing pin in contact location 15

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.049 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc and unc and unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.