NSN 5935-01-174-1136

Thread Class: 2a and 2b and 2a

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-174-1136

Thread Direction: Right-hand and right-hand and right-hand **Body Style:** Straight shape **Overall Length:** 2.850 inches **Overall Height:** 0.723 inches **Overall Width:** 0.250 inches **Environmental Protection:** Cold resistant and heat resistant **Distance Between Mounting Facility Centers:** 2.650 inches **Threaded Device Type:** Coupling facility and mounting stud **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Jackscrew **Connector Locking Method:** Jackscrew-socket Thready Qty Per Inch (tpi): 56 and 56 and 56 **Thread Size:** 0.086 inches and 0.086 inches and 0.086 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic polyphenylene single mating end

NSN 5935-01-174-1136

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Criticality Code Justification:

Feat

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-24519 military specification single material response single mating end

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

49 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

0.060 in. Diameter polarizing pin in contact location 21

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.049 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc and unc and unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.