# NSN 5935-01-174-1138

Thread Class: 2a and 2b and 2a

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-174-1138

Thread Direction:
Right-hand and right-hand and right-hand
Body Style:
Straight shape
Overall Length:
2.850 inches
Overall Height:
0.723 inches
Overall Width:
0.250 inches
Environmental Protection:
Cold resistant and heat resistant
Distance Between Mounting Facility Centers:
2.650 inches
Threaded Device Type:
Coupling facility and mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Connector Locking Method:
Jackscrew-socket
Thready Qty Per Inch (tpi):
56 and 56 and 56
Thread Size:
0.086 inches and 0.086 inches and 0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic polyphenylene single mating end

# NSN 5935-01-174-1138

Electrical Receptacle Connector - Page 2 of 2



#### **Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Criticality Code Justification:** 

Feat

# **Terminal Type:**

Pin single mating end single contact grouping

# **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

#### **Insert Material Specification:**

Mil-m-24519 military specification single material response single mating end

#### **Unable To Decode:**

Unable to decode and unable to decode

#### **Included Contact Quantity:**

49 single mating end single contact grouping

#### **Included Contact Type:**

Round pin single mating end single contact grouping

#### **Special Features:**

0.060 in. Diameter polarizing pin in contact location 18

#### **Precious Material And Location:**

Contact surfaces gold

# **Precious Material And Weight:**

0.049 gold grains, troy

# **Precious Material:**

Gold

# **Thread Series Designator:**

Unc and unc and unc

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.