

View Online at <https://aerobasegroup.com/nsn/5935-01-174-1144>

Thread Class:

2a and 2a and 2a

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

Straight shape, external coupling w/strain relief

Overall Diameter:

1.750 inches

Environmental Protection:

Moisture resistant and thermal shock resistant and vibration resistant

Cable Entrance Diameter:

0.625 inches

Distance From Mounting Shoulder To Front Face:

1.030 inches

Threaded Device Type:

Mounting bushing and back shell

Mating End Quantity:

12

Polarization Method:

Keyway or multiple keyway and polarization boss

Insert Position In Deg:

0.0 and 95.0 and 132.0 and 232.0 and 260.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Connector Cable Strain Relief Method:

Cable clamp and cord protector

Thready Qty Per Inch (tpi):

18 and 16

Thread Size:

1.500 inches and 1.625 inches

Insert Material:

Rubber single mating end

Shell Material:

Aluminum

Bushing Accommodation Hole Shape:

Round w/flat

Thread Series Designator:

Unef and uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0