NSN 5935-01-174-6111

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-174-6111

Body Style:
Straight type
Overall Length:
3.900 inches
Overall Height:
0.462 inches
Overall Width:
0.400 inches
Environmental Protection:
Humidity resistant and salt water resistant and shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
3.623 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
92 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Guide pin/socket
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic polyphenylene single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, class 1, grade c military specification single treatment response single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Contact Material Specification:
Qq-c-530 federal specification single material response single mating end single contact grouping
Guide Design And Location:

Insert Material Specification:

Hexagon shape male post right-hand at 3 oclock

Mil-m-24519 military specification single material response single mating end

NSN 5935-01-174-6111

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:
92 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.092 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.