## NSN 5935-01-174-7727

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-174-7727

Body Style:
Straight shape
Overall Length:
4.466 inches
Overall Height:
0.796 inches
Overall Width:
0.562 inches
Environmental Protection:
Corrosion resistant and moisture proof and shock resistant and vibration proof
Unthreaded Mounting Hole Diameter:
Between 0.139 inches and 0.149 inches
Distance Between Mounting Facility Centers:
Between 3.990 inches and 4.010 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
29 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
650.0 single mating end single contact grouping
Polarization Method:
Shell
Shell Type:
Solid
Connector Locking Method:
Friction
End Application:
Radar set, an/tpn-22
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping

## NSN 5935-01-174-7727

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416 federal specification single treatment response
Shell Material Specification:
Qq-a-591 federal specification single material response
Insert Material Specification:
Mil-p-19833b ty gd1-30f military specification single material response single mating end or mil-m-14f ty sdg-f military specification single
material response single mating end
Included Contact Quantity:
29 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.029 gold grains, troy and 0.029 silver grains, troy
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-p-19833b spec.