NSN 5935-01-175-1799

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-175-1799

specification 2nd treatment response single mating end single contact grouping

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Right angle type
Overall Length:
2.956 inches
Overall Height:
0.817 inches
Environmental Protection:
Corrosion resistant and moisture resistant and shock resistant and vibration resistant
Distance Between Mounting Facility Centers:
2.776 inches
Threaded Device Type:
Mounting hole
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket and contact
Connector Locking Method:
Friction
Thready Qty Per Inch (tpi):
40
Thread Size:
0.112 inches
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2 military specification 1st treatment response single mating end single contact grouping and qq-n-290, class 2 federal

NSN 5935-01-175-1799

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Pin single mating end single contact grouping
Contact Material Specification:
Qq-b-750, comp a federal specification single material response single mating end single contact grouping
Insert Material Specification:
Mil-m-14, type sdg military specification single material response single mating end
Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:
31 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.031 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.