Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-175-1799

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Right angle type

Overall Length:

2.956 inches

Overall Height:

0.817 inches

Environmental Protection:

Corrosion resistant and moisture resistant and shock resistant and vibration resistant

Distance Between Mounting Facility Centers:

2.776 inches

Threaded Device Type:

Mounting hole

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket and contact

Connector Locking Method:

Friction

Thready Qty Per Inch (tpi):

40

Thread Size:

0.112 inches

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2 military specification 1st treatment response single mating end single contact grouping and qq-n-290, class 2 federal

specification 2nd treatment response single mating end single contact grouping



Pin single m	nating end single contact grouping
Contact Ma	aterial Specification:
Qq-b-750, c	comp a federal specification single material response single mating end single contact grouping
Insert Mate	erial Specification:
Mil-m-14, ty	pe sdg military specification single material response single mating end
Unable To	Decode:
Unable to de	ecode and unable to decode
Included Co	ontact Quantity:
31 single ma	ating end single contact grouping
Included Co	ontact Type:
Round pin s	single mating end single contact grouping
Precious M	laterial And Location:
Contact sur	faces gold
Precious M	laterial And Weight:
0.031 gold g	grains, troy
Precious M	laterial:
Gold	
Thread Ser	ries Designator:
Unc	
Shelf Life:	
N/a	
Unit Of Mea	asure:
Demilitariza	ation:
No	
Fiig:	
A039b0	
Mil-std (mil	litary Standard):
Mil-g-45204	l spec.