

View Online at <https://aerobasegroup.com/nsn/5935-01-175-5035>

**Body Material:**

Plastic

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Bottom mount w/metal saddle and bushings

**Overall Length:**

1.570 inches

**Overall Height:**

0.719 inches

**Overall Width:**

0.730 inches

**Mounting Hole Diameter:**

0.161 inches

**Body Mounting Hole Accommodation Diameter:**

0.730 inches

**Distance Between Mounting Facility Centers:**

1.187 inches

**Mounting Hole Style:**

Round, w/two mounting holes

**Contact Maximum Current Rating In Amps:**

10.0

**Contact Material:**

Beryllium copper

**Contact Surface Treatment:**

Gold and nickel

**Accommodated Contact Quantity:**

2

**End Application:**

2350-01-089-1261

**Polarization Type:**

Contact position

**Projection Length Above Mounting Surface:**

0.028 inches

**Mounting Method:**

Threaded hole

**Mounting Type For Which Designed:**

Chassis

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.138 inches

**Contact Position Arrangement Style:**

In line

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.010 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-s-12883 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

2 tab, solder lug

**Specification Data:**

81349-mil-s-12883/42 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A02300