

View Online at https://aerobasegroup.com/nsn/5935-01-175-5035

E	Body Material:
F	Plastic
٦	Thread Class:
2	b
٦	Thread Direction:
F	Right-hand
E	Body Style:
E	Bottom mount w/metal saddle and bushings
C	Overall Length:
1	.570 inches
C	Overall Height:
C	0.719 inches
C	Overall Width:
C	0.730 inches
N	Nounting Hole Diameter:
C	0.161 inches
E	Body Mounting Hole Accommodation Diameter:
C	0.730 inches
۵	Distance Between Mounting Facility Centers:
1	.187 inches
N	Nounting Hole Style:
F	Round, w/two mounting holes
C	Contact Maximum Current Rating In Amps:
1	0.0
C	Contact Material:
E	Beryllium copper
C	Contact Surface Treatment:
C	Gold and nickel
ł	Accommodated Contact Quantity:
2	2
E	End Application:
2	2350-01-089-1261
F	Polarization Type:
C	Contact position
F	Projection Length Above Mounting Surface:
C	0.028 inches
N	Nounting Method:
٦	Threaded hole
N	Nounting Type For Which Designed:
C	Chassis
٦	Thready Qty Per Inch (tpi):
2	19

32



Thread Size:

0.138 inches

Contact Position Arrangement Style:

In line

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-s-12883 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 tab, solder lug

Specification Data:

81349-mil-s-12883/42 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A02300