NSN 5935-01-175-8216

Electrical Plug Connector - Page 1 of 2



| view Online at https://aerobasegroup.com/nsn/5935-01-175-6216 | | |
|---|--|--|
| Body Style: | | |
| Straight shape | | |
| Overall Length: | | |
| 2.690 inches | | |
| Overall Width: | | |
| 0.240 inches | | |
| Mating End Quantity: | | |
| 1 | | |
| Contact Position Arrangement Style: | | |
| 2 rows of contacts non-inserted board single mating end | | |
| Contact Removability: | | |
| Removable single mating end single contact grouping | | |
| Contact Maximum Current Rating In Amps: | | |
| 1.0 single mating end single contact grouping | | |
| Polarization Method: | | |
| Key, multiple key groove | | |
| Insert Position In Deg: | | |
| 0.0 | | |
| Connector Locking Method: | | |
| Friction | | |
| Connector Cable Strain Relief Method: | | |
| Crimp type | | |
| Terminal Location: | | |
| Back single mating end single contact grouping | | |
| Contact Material: | | |
| Copper alloy single mating end single contact grouping | | |
| Contact Surface Treatment: | | |
| Gold single mating end single contact grouping and nickel single mating end single contact grouping | | |
| Insert Material: | | |
| Plastic single mating end | | |
| Terminal Type: | | |
| Crimp single mating end single contact grouping | | |
| Included Contact Quantity: | | |
| 50 single mating end single contact grouping | | |
| Included Contact Type: | | |
| Flat socket single mating end single contact grouping | | |
| Precious Material And Location: | | |
| Contact surfaces gold | | |
| Precious Material And Weight: | | |
| 0.050 gold grains, troy | | |

Gold

Precious Material:

NSN 5935-01-175-8216

Electrical Plug Connector - Page 2 of 2



| | Life: |
|--|-------|
| | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0