Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-175-8271

### **Body Style:**

Straight shape

### **Overall Length:**

Between 1.198 inches and 1.228 inches

## **Overall Height:**

0.639 inches

### **Overall Width:**

Between 0.479 inches and 0.509 inches

#### **Environmental Protection:**

Corrosion resistant and humidity resistant and shock resistant and vibration resistant

#### **Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.125 inches

#### Distance Between Mounting Facility Centers:

Between 0.979 inches and 0.989 inches

#### Mating End Quantity:

**Contact Position Arrangement Style:** 

9 single mating end

### **Contact Removability:**

Nonremovable single mating end single contact grouping

### **Polarization Method:**

Mating end

Shell Type:

Solid

1

### **Connector Locking Method:**

Friction

### **Operating Tempurature Rating:**

Between -55.0 degrees celsius and 125.0 degrees celsius

### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

# Insert Material:

Plastic diallyl phthalate glass filled single mating end or plastic polyester glass filled single mating end

# Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2

federal specification 2nd treatment response single mating end single contact grouping

# Criticality Code Justification:

Feat

#### Terminal Type:

Pin single mating end single contact grouping



**Shell Material:** Metal Shell Surface Treatment: Cadmium and chromate Shell Surface Treatment Specification: Qq-p-416, type 2, cl 2 federal specification all treatment responses **Insert Material Specification:** Mil-m-14, ty sdg-f military specification 1st material response single mating end or mil-m-24519, ty gpt-30f or ty get-30f military specification 2nd material response single mating end **Included Contact Quantity:** 9 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Special Features:** Pin terminal diameter 0.037 min to 0.043 max **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.009 gold grains, troy **Precious Material:** Gold **Test Data Document:** 81349-mil-c-24308 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Data:** 81349-mil-c-24308/24 government specification Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.