## NSN 5935-01-175-8296

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-175-8296 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 2.672 inches **Overall Height:** Between 1.146 inches and 1.170 inches **Overall Width:** Between 3.000 inches and 3.030 inches **Environmental Protection:** Salt spray proof and thermal shock resistant and vibration resistant and shock resistant and moisture resistant and solvent resistant and fuel **Unthreaded Mounting Hole Diameter:** Between 0.144 inches and 0.148 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.558 inches and 0.566 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 2.570 inches and 2.580 inches **Distance From Mounting Shoulder To Front Face:** Between 0.615 inches and 0.630 inches **Threaded Device Type:** Mounting hole **Mating End Quantity: Contact Position Arrangement Style:** G131 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Connector Locking Method:** Friction

32

Thread Size:

**Operating Tempurature Rating:** 

Thready Qty Per Inch (tpi):

Between -54.0 degrees celsius and 200.0 degrees celsius

0.138 inches

# NSN 5935-01-175-8296

Electrical Receptacle Connector - Page 2 of 2



#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping and copper single mating end single contact grouping

#### **Insert Material:**

Plastic single mating end and glass single mating end

### **Contact Surface Treatment Specification:**

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping

#### **Terminal Type:**

Crimp single mating end single contact grouping

#### **Contact Material Specification:**

Qq-c-533 federal specification single material response single mating end single contact grouping

#### **Shell Material:**

Aluminum alloy 380.0

#### **Shell Surface Treatment:**

Nickel

### **Shell Surface Treatment Specification:**

Mil-c-26074, cl 3 military specification single treatment response

#### **Shell Material Specification:**

Qq-a-591 federal specification single material response

### **Included Contact Quantity:**

131 single mating end single contact grouping

### **Included Contact Type:**

Round socket single mating end single contact grouping

### **Precious Material And Location:**

Contact surfaces gold

### **Precious Material And Weight:**

0.131 gold grains, troy

#### **Precious Material:**

Gold

### **Thread Series Designator:**

Unc

### Shelf Life:

N/a

#### **Unit Of Measure:**

### Demilitarization:

No

## Fiig:

A039b0

#### Mil-std (military Standard):

Mil-g-45204 spec.