NSN 5935-01-175-8305

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-175-8305
Body Style:
Straight shape, flush mount
Overall Length:
1.061 inches
Overall Height:
3.075 inches
Overall Width:
2.000 inches
Environmental Protection:
Cold resistant and heat resistant
Unthreaded Mounting Hole Diameter:
Between 0.114 inches and 0.118 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
2.783 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.437 inches
Distance From Mounting Shoulder To Front Face:
0.060 inches
Mating End Quantity:
2
Contact Position Arrangement Style:
57 all mating ends
Contact Removability:
Removable all mating ends single contact grouping
Contact Maximum Current Rating In Amps:
5.0 all mating ends single contact grouping
Polarization Method:
3 polarization posts
Shell Type:
Solid
Connector Locking Method:

Friction

Terminal Location:

Back all mating ends single contact grouping

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping

Insert Material:

Plastic diallyl phthalate all mating ends

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response all mating ends single contact grouping

NSN 5935-01-175-8305

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Crimp all mating ends single contact grouping
Contact Material Specification:
Qq-c-533 federal specification single material response all mating ends single contact grouping
Guide Design And Location:
Hexagon shape female post left-hand at 12 oclock and hexagon shape female post center at 12 oclock and hexagon shape female post
right-hand at 12 oclock
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416 federal specification all treatment responses
Shell Material Specification:
Qq-a-591 federal specification single material response
Included Contact Type:
Round socket all mating ends single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.114 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No Fiig: A039b0

Mil-std (military Standard):

Mil-g-45204 spec.