

View Online at <https://aerobasegroup.com/nsn/5935-01-176-0749>

Body Style:

Straight edge type w/mounting flange

Overall Length:

2.478 inches

Overall Height:

0.704 inches

Overall Width:

0.346 inches

Unthreaded Mounting Hole Diameter:

0.112 inches

Distance Between Mounting Facility Centers:

2.156 inches

Board Accommodated Length:

1.715 inches single board

Board Accommodated Width:

Between 0.054 inches and 0.071 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end single contact grouping

Polarization Method:

Mating end

Connector Locking Method:

Friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic phenolic single mating end

Terminal Type:

Tab, solder lug single mating end single contact grouping

Included Contact Quantity:

20 single mating end single contact grouping

Included Contact Type:

Bifurcated spring single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.020 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0