NSN 5935-01-176-1658

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-176-1658

Body Style:
Straight shape
Overall Length:
2.088 inches
Overall Height:
0.701 inches
Overall Width:
0.494 inches
Environmental Protection:
Corrosion resistant and moisture resistant and shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
1.852 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
21 single mating end
Contact Removability:
Nonremovable single mating end 1st contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end 1st contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Spring friction
Terminal Location:
Back single mating end 1st contact grouping
Contact Material:
Copper alloy single mating end 1st contact grouping
Contact Surface Treatment:
Gold single mating end 1st contact grouping and silver single mating end 1st contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification 1st treatment response single mating end 1st contact grouping and qq-s-365 federal specification 2nd
treatment response single mating end 1st contact grouping
Terminal Type:
Solder well single mating end 1st contact grouping

Steel

Shell Material:

NSN 5935-01-176-1658

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification single treatment response
Shell Material Specification:
Qq-s-698 federal specification single material response
Insert Material Specification:
Mil-p-19833, ty gdi-30f military specification single material response single mating end or mil-m-14, ty sdg-f military specification single
material response single mating end
Included Contact Quantity:
20 single mating end 1st contact grouping
Included Contact Type:
Round pin single mating end 1st contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.020 gold grains, troy and 0.020 silver grains, troy
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.