

View Online at <https://aerobasegroup.com/nsn/5935-01-176-1669>

**Thread Class:**

2a and 2a

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

2.156 inches

**Overall Diameter:**

1.375 inches

**Environmental Protection:**

Vibration resistant

**Distance From Mounting Shoulder To Front Face:**

1.665 inches

**Mounting Facility Thickness:**

Between 0.125 inches and 0.750 inches

**Threaded Device Type:**

Back shell and mounting bushing

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

13-98 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

600.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

850.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

340.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**Thread Length:**

0.219 inches

**Thready Qty Per Inch (tpi):**

24 and 20

**Thread Size:**

0.688 inches and 1.000 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Nickel

**Included Contact Quantity:**

10 single mating end single contact grouping

**Bushing Accommodation Hole Shape:**

Round w/flat

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.010 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unef and unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.