

View Online at <https://aerobasegroup.com/nsn/5935-01-176-7189>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Angle shape w/cable clamp

Overall Diameter:

2.469 inches

Body Angle In Deg:

135.0

Environmental Protection:

Moisture proof and salt water resistant and vibration proof and shock resistant and cold resistant and moisture proof and explosion proof

Cable Entrance Diameter:

Between 0.500 inches and 0.750 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

36-15 single mating end

Contact Removability:

Removable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

22.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

900.0 single mating end 1st contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end 2nd contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring

Connector Cable Strain Relief Method:

Cable clamp

Distance From Centerline To Connector End:

3.125 inches

Distance From Centerline To Cable End:

3.875 inches

Operating Temperature Rating:

Between -55.0 degrees celsius and 175.0 degrees celsius

Thready Qty Per Inch (tpi):

16

Thread Size:

2.250 inches

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings

Insert Material:

Rubber silicone class q single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end all contact groupings

Criticality Code Justification:

Feat

Terminal Type:

Crimp single mating end all contact groupings

Shell Material:

Aluminum

Shell Surface Treatment:

Cadmium and chromate and nickel

Shell Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification 1st treatment response and qq-p-416, type 2, class 3 federal specification 2nd treatment response

Included Contact Quantity:

34 single mating end 2nd contact grouping

Included Contact Type:

Round pin single mating end all contact groupings

Special Features:

16-22 wire size pin contacts in lieu of 16-16

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.035 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Un

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.