

View Online at <https://aerobasegroup.com/nsn/5935-01-177-1294>

**Body Style:**

Straight shape

**Overall Length:**

1.541 inches

**Overall Height:**

Between 3.095 inches and 3.125 inches

**Overall Width:**

Between 1.985 inches and 2.015 inches

**Environmental Protection:**

Humidity resistant and salt water resistant and shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

Between 0.118 inches and 0.122 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

2.783 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.437 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.764 inches and 0.768 inches

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

26 all mating ends

**Contact Removability:**

Removable all mating ends single contact grouping

**Polarization Method:**

Shell

**Shell Type:**

Solid

**Terminal Location:**

Back all mating ends single contact grouping

**Contact Material:**

Copper alloy all mating ends single contact grouping

**Contact Surface Treatment:**

Gold all mating ends single contact grouping

**Insert Material:**

Plastic diallyl phthalate all mating ends or plastic epoxy all mating ends or plastic phenolic all mating ends

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response all mating ends single contact grouping

**Terminal Type:**

Crimp all mating ends single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium and chromate

**Shell Surface Treatment Specification:**

Qq-p-416 federal specification all treatment responses

**Shell Material Specification:**

Qq-a-591 federal specification single material response or qq-a-367 federal specification single material response or qq-a-250 federal specification single material response

**Insert Material Specification:**

Mil-m-14 military specification single material response all mating ends or 1288bx mfr ref single material response all mating ends

**Included Contact Type:**

Round socket all mating ends single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.052 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-81659 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-c-81659/33 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.