

View Online at <https://aerobasegroup.com/nsn/5935-01-177-1297>

**Body Style:**

Straight type

**Overall Length:**

11.295 inches

**Overall Height:**

1.100 inches

**Overall Width:**

0.590 inches

**Environmental Protection:**

Moisture resistant and shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

0.122 inches

**Distance Between Mounting Facility Centers:**

10.975 inches

**Mating End Quantity:**

1

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

1300.0 single mating end single contact grouping

**Polarization Method:**

Contact

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic polyester single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type ii military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Wire wrap single mating end single contact grouping

**Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

**Included Contact Quantity:**

400 single mating end single contact grouping

**Special Features:**

Four rows of contacts with 100 contacts in each row

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.400 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.