

View Online at <https://aerobasegroup.com/nsn/5935-01-177-9089>

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

2.125 inches

Overall Diameter:

Between 1.318 inches and 1.380 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

18-11 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

41.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

170.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thread Length:

0.290 inches and 0.625 inches

Thready Qty Per Inch (tpi):

18 and 18

Thread Size:

1.062 inches and 1.125 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Rubber silicone class q single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification all treatment responses

Included Contact Quantity:

5 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.025 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef and unef

Specification Data:

96906-ms3401 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.