

View Online at <https://aerobasegroup.com/nsn/5935-01-178-2568>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight type

Overall Length:

3.950 inches

Overall Height:

0.625 inches

Overall Width:

0.280 inches

Environmental Protection:

Moisture resistant and shock resistant and salt water resistant and thermal shock resistant and vibration resistant

Distance Between Mounting Facility Centers:

3.700 inches

Threaded Device Type:

Mounting hole

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

150.0 single mating end single contact grouping

Polarization Method:

Mating end

Shell Type:

Solid

Connector Locking Method:

Friction

Thready Qty Per Inch (tpi):

40

Thread Size:

0.112 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 1 military specification 1st treatment response single mating end single contact grouping

Contact Material Specification:

Astm b-140 assn standard single material response single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Nickel

Shell Surface Treatment Specification:

Mil-c-26074, class 3 military specification single treatment response

Shell Material Specification:

Qq-a-591 federal specification single material response

Insert Material Specification:

Mil-m-14, type sgd-f military specification single material response single mating end

Included Contact Quantity:

128 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact and terminal surfaces gold

Precious Material And Weight:

0.128 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.