## NSN 5935-01-178-2573

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-178-2573

**Body Style:** Right angle type **Overall Length:** Between 3.390 inches and 3.550 inches **Overall Height:** 0.960 inches **Overall Width:** 0.910 inches **Unthreaded Mounting Hole Diameter:** 0.086 inches **Distance Between Mounting Facility Centers:** 2.360 inches **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 1.0 single mating end single contact grouping **Polarization Method:** Shell **Connector Locking Method:** Latch **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Glass single mating end and plastic polyester single mating end **Contact Surface Treatment Specification:** Mil-g-45204, type 2 military specification 1st treatment response single mating end single contact grouping **Terminal Type:** Pin single mating end single contact grouping **Included Contact Quantity:** 40 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping

Contact surfaces gold

**Precious Material And Location:** 

## NSN 5935-01-178-2573

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Weight:
0.040 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.