# NSN 5935-01-178-4259

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-178-4259
Thread Class:
2a and 2b and 2a
Thread Direction:
Right-hand and right-hand and right-hand
Body Style:
Straight shape
Overall Length:
3.850 inches
Overall Height:
0.712 inches
Overall Width:
0.250 inches
Distance Between Mounting Facility Centers:
3.650 inches
Threaded Device Type:
Coupling facility and mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Connector Locking Method:
Jackscrew-socket
Thready Qty Per Inch (tpi):
56 and 56 and 56
Thread Size:

0.086 inches and 0.086 inches and 0.086 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Glass single mating end and plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204 military specification single treatment response single mating end single contact grouping

# NSN 5935-01-178-4259

Electrical Receptacle Connector - Page 2 of 2



#### **Terminal Type:**

Tab, solder lug single mating end single contact grouping

#### **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

#### **Insert Material Specification:**

Mil-p-19833 military specification all material responses single mating end or mil-m-14f military specification all material responses single mating end

#### **Included Contact Quantity:**

70 single mating end single contact grouping

#### **Included Contact Type:**

Round pin single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.070 gold grains, troy

#### **Precious Material:**

Gold

#### **Thread Series Designator:**

Unc and unc and unc

#### Shelf Life:

N/a

#### **Unit Of Measure:**

--

### Demilitarization:

No

## Fiig:

A039b0

### Mil-std (military Standard):

Mil-g-45204 spec.