NSN 5935-01-178-4263

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-178-4263

Body Style:

Straight shape, external coupling strain relief

Overall Height:

1.438 inches

Overall Width:

1.438 inches

Body Length:

2.125 inches

Environmental Protection:

Corrosion resistant and humidity resistant and moisture resistant and shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.115 inches and 0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.187 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Distance De

1.187 inches

Cable Entrance Diameter:

0.750 inches

Distance From Mounting Shoulder To Front Face:

0.531 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

37-27p single mating end

Contact Removability:

Removable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

7.5 single mating end 1st contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Spring friction

Connector Cable Strain Relief Method:

Cable clamp

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings



Contact Sur	face Treatment:
Gold single n	nating end all contact groupings
Insert Mater	ial:
Rubber synth	netic single mating end
Contact Sur	face Treatment Specification:
Mil-g-45204 ı	military specification single treatment response single mating end all contact grouping
Terminal Ty	pe:
Crimp single	mating end all contact groupings
Shell Materi	al:
Aluminum all	оу
Shell Surfac	e Treatment:
Cadmium	
Shell Surfac	e Treatment Specification:
Qq-p-416, ty	be 11, class 2 federal specification single treatment response
Included Co	ntact Quantity:
7 single mati	ng end 2nd contact grouping
Included Co	ntact Type:
Round pin si	ngle mating end 1st contact grouping
Precious Ma	terial And Location:
Contact surfa	aces gold
Precious Ma	terial And Weight:
0.013 gold gi	ains, troy
Precious Ma	iterial:
Gold	
Shelf Life:	
N/a	
Unit Of Mea	sure:
Demilitariza	tion:
No	
Fiig:	
A039b0	
Mil-std (mili	ary Standard):
Mil-g-45204 :	SDEC.