NSN 5935-01-178-8297

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-178-8297

Body Style:
Straight type
Overall Length:
3.470 inches
Overall Height:
0.506 inches
Overall Width:
0.342 inches
Unthreaded Mounting Hole Diameter:
0.093 inches
Distance Between Mounting Facility Centers:
3.290 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, class 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290
federal specification 2nd treatment response single mating end single contact grouping
Criticality Code Justification:
Feat
Terminal Type:
Tab, solder lug single mating end single contact grouping
Insert Material Specification:
Mil-m-14, ty sdgf military specification single material response single mating end
Included Contact Quantity:

Special Features:

Contacts without shoulder

Included Contact Type:

120 single mating end single contact grouping

Round pin single mating end single contact grouping

NSN 5935-01-178-8297

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.120 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.