## NSN 5935-01-178-8398

Electrical Receptacle Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-178-8398
Thread Class:
2a and 2a and 2a
Thread Direction:
Right-hand and right-hand and right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.662 inches
Overall Height:
1.500 inches
Overall Width:
1.500 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration proof and corrosion resistant and dust resistant and fuel resistant and fungus resistant
and humidity resistant and oil resistant and shock resistant and thermal shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.156 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.156 inches
Distance From Mounting Shoulder To Front Face:
0.750 inches
Threaded Device Type:
Coupling facility and back shell
Mating End Quantity:
12
Contact Position Arrangement Style:
20-27 single mating end
Polarization Method:
Keyway or multiple keyway and polarization boss
Insert Position In Deg:
35.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
18 and 16
Thread Size:

Rubber single mating end

**Insert Material:** 

1.250 inches and 0.938 inches

## NSN 5935-01-178-8398

A039b0

Mil-c-5015 spec.

Mil-std (military Standard):

Electrical Receptacle Connector Body - Page 2 of 2



Shell Material:
Aluminum alloy or zinc
Shell Surface Treatment:
Cadmium and chromate and zinc
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Test Data Document:
81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef and uns
Specification Data:
96906-ms3402 government standard
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig: