## NSN 5935-01-178-8400

Electrical Receptacle Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-178-8400

Thread Class:
2a and 2a and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.662 inches
Overall Height:
2.750 inches
Overall Width:
2.750 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration proof and corrosion resistant and dust resistant and fuel resistant and fungus resistant
and humidity resistant and oil resistant and shock resistant and thermal shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.173 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
2.188 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
2.188 inches
Distance From Mounting Shoulder To Front Face:
0.875 inches
Threaded Device Type:
Coupling facility and back shell
Mating End Quantity:
12
Contact Position Arrangement Style:
40-56 single mating end
Polarization Method:
Keyway or multiple keyway and polarization boss
Insert Position In Deg:
216.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
16 and 10 and 16
Thread Size:

Insert Material:

Rubber single mating end

2.500 inches and 2.500 inches

## NSN 5935-01-178-8400

Electrical Receptacle Connector Body - Page 2 of 2



Shell Material:
Aluminum alloy or zinc
Shell Surface Treatme
Cadmium and chromate
Shell Surface Treatme
Qq-p-416, type 2, cl 3
<b>Test Data Document:</b>
81349-mil-c-5015 spec
format; excludes comm
environmental and perf

ent:

te and zinc

ent Specification:

federal specification single treatment response

ification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification nercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain formance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Thread Series Designator:**

Un and double stub and un

**Specification Data:** 

96906-ms3402 government standard

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-5015 spec.