Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-179-0358

#### **Body Style:**

Straight type

**Overall Length:** 

4.900 inches

### **Overall Height:**

0.677 inches

### **Overall Width:**

0.400 inches

### **Environmental Protection:**

Vibration resistant and shock resistant and salt water resistant and humidity resistant and thermal shock resistant

### **Unthreaded Mounting Hole Diameter:**

0.120 inches

### **Distance Between Mounting Facility Centers:**

4.650 inches

### Mating End Quantity:

1

### **Contact Position Arrangement Style:**

3 rows of contacts non-inserted board single mating end

### Contact Removability:

Nonremovable single mating end single contact grouping

### **Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

## **Polarization Method:**

Guide pin/socket

### **Connector Locking Method:**

Friction

### **Operating Tempurature Rating:**

Between -65.0 degrees celsius and 125.0 degrees celsius

### **Terminal Location:**

Back single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping

# Insert Material:

Plastic polyphenylene single mating end

# Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

# **Terminal Type:**

Pin single mating end single contact grouping

# **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single

material response single mating end single contact grouping



# Guide Design And Location:

D shape socket right-hand at 9 oclock and d shape pin right-hand at 9 oclock

### **Insert Material Specification:**

Mil-m-24519 military specification single material response single mating end

### Included Contact Quantity:

122 single mating end single contact grouping

### Included Contact Type:

Round socket single mating end single contact grouping

### **Precious Material And Location:**

Contact surfaces gold

### **Precious Material And Weight:**

0.122 gold grains, troy

Precious Material:

Gold

### **Specification Data:**

82577-657749 manufacturers specification control

### Shelf Life:

N/a

### Unit Of Measure:

Demilitarization:

No

---

Fiig:

A039b0

## Mil-std (military Standard):

Mil-g-45204 spec.