NSN 5935-01-179-0361

60 single mating end single contact grouping

Electrical Receptacle Connector - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5955-01-179-0361
Body Style:
Right angle type
Overall Length:
3.760 inches
Overall Height:
1.300 inches
Overall Width:
0.550 inches
Environmental Protection:
Humidity resistant and shock resistant and thermal shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.093 inches and 0.105 inches
Distance Between Mounting Facility Centers:
3.600 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
1.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
300.0 single mating end single contact grouping
Polarization Method:
Contact
Connector Locking Method:
Latch
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic polyester single mating end
Terminal Type:
Wire wrap single mating end single contact grouping
Insert Material Specification:
Mil-m-24519, ty gpt-15f or gpt-20f or gpt-30f military specification single material response single mating end
Included Contact Quantity:

NSN 5935-01-179-0361

Mil-std (military Standard):

Mil-m-24519 spec.

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.060 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-83503 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-83503/20 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
Δ ∩ 39h ∩