## NSN 5935-01-179-7895

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-179-7895

view Orimite at https://derobasegroup.com/nsi//0900-01-179-7090
Body Style:
Straight shape, internal coupling w/strain relief
Body Length:
0.219 inches
Overall Diameter:
1.484 inches
Environmental Protection:
Shock resistant and vibration resistant and corrosion resistant and moisture resistant
Cable Entrance Diameter:
1.875 inches
Mating End Quantity:
1
Contact Removability:
Removable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
7.5 single mating end 2nd contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
150.0
Shell Type:
Solid
Connector Locking Method:
Spring friction
Connector Cable Strain Relief Method:
Cable clamp
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings and silver single mating end all contact groupings
Insert Material:
Rubber single mating end
Terminal Type:
Crimp single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate

Included Contact Quantity:

4 single mating end 1st contact grouping

## NSN 5935-01-179-7895

Electrical Plug Connector - Page 2 of 2



## **Included Contact Type:**

Round pin single mating end 2nd contact grouping

**Precious Material And Location:** 

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:** 

0.040 gold grains, troy and 0.040 silver grains, troy

**Precious Material:** 

Gold and silver

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0