Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-179-7898

Thread Class:
2a
Thread Direction:
Right-hand
Overall Length:
1.000 inches
Overall Diameter:
0.600 inches
Threaded Device Type:
Mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
Tps single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Bayonet latch
Bayonet latch Radio Frequency Type Contact Characteristic Impedance In Ohms:
Radio Frequency Type Contact Characteristic Impedance In Ohms:
Radio Frequency Type Contact Characteristic Impedance In Ohms:50.0 single mating end single contact grouping
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thread Size:
Radio Frequency Type Contact Characteristic Impedance In Ohms:         50.0 single mating end single contact grouping         Thread Size:         0.438 inches
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thread Size: 0.438 inches Terminal Location:
Radio Frequency Type Contact Characteristic Impedance In Ohms:         50.0 single mating end single contact grouping         Thread Size:         0.438 inches         Terminal Location:         Back single mating end single contact grouping
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thread Size: 0.438 inches Terminal Location: Back single mating end single contact grouping Contact Material:
Radio Frequency Type Contact Characteristic Impedance In Ohms:50.0 single mating end single contact groupingThread Size:0.438 inchesTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact grouping
Radio Frequency Type Contact Characteristic Impedance In Ohms:50.0 single mating end single contact groupingThread Size:0.438 inchesTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingContact Surface Treatment:
Radio Frequency Type Contact Characteristic Impedance In Ohms:50.0 single mating end single contact groupingThread Size:0.438 inchesTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingContact Surface Treatment:Gold single mating end single contact grouping
Radio Frequency Type Contact Characteristic Impedance In Ohms:50.0 single mating end single contact groupingThread Size:0.438 inchesTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingContact Surface Treatment:Gold single mating end single contact groupingInsert Material:
Radio Frequency Type Contact Characteristic Impedance In Ohms:50.0 single mating end single contact groupingThread Size:0.438 inchesTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingContact Surface Treatment:Gold single mating end single contact groupingInsert Material:Plastic polytetrafluoroethylene single mating end
Radio Frequency Type Contact Characteristic Impedance In Ohms:50.0 single mating end single contact groupingThread Size:0.438 inchesTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingContact Surface Treatment:Gold single mating end single contact groupingInsert Material:Plastic polytetrafluoroethylene single mating endTerminal Type:
Radio Frequency Type Contact Characteristic Impedance In Ohms:50.0 single mating end single contact groupingThread Size:0.438 inchesTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingContact Surface Treatment:Gold single mating end single contact groupingInsert Material:Plastic polytetrafluoroethylene single mating endTerminal Type:Solder well single mating end single contact grouping
<ul> <li>Radio Frequency Type Contact Characteristic Impedance In Ohms:</li> <li>50.0 single mating end single contact grouping</li> <li>Thread Size:</li> <li>0.438 inches</li> <li>Terminal Location:</li> <li>Back single mating end single contact grouping</li> <li>Contact Material:</li> <li>Copper alloy single mating end single contact grouping</li> <li>Contact Surface Treatment:</li> <li>Gold single mating end single contact grouping</li> <li>Insert Material:</li> <li>Plastic polytetrafluoroethylene single mating end</li> <li>Terminal Type:</li> <li>Solder well single mating end single contact grouping</li> </ul>
Radio Frequency Type Contact Characteristic Impedance In Ohms:50.0 single mating end single contact groupingThread Size:0.438 inchesTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingContact Surface Treatment:Gold single mating end single contact groupingInsert Material:Plastic polytetrafluoroethylene single mating endTerminal Type:Solder well single mating end single contact groupingShell Material:Copper alloy
<ul> <li>Radio Frequency Type Contact Characteristic Impedance In Ohms:</li> <li>50.0 single mating end single contact grouping</li> <li>Thread Size:</li> <li>0.438 inches</li> <li>Terminal Location:</li> <li>Back single mating end single contact grouping</li> <li>Contact Material:</li> <li>Copper alloy single mating end single contact grouping</li> <li>Contact Surface Treatment:</li> <li>Gold single mating end single contact grouping</li> <li>Insert Material:</li> <li>Plastic polytetrafluoroethylene single mating end</li> <li>Terminal Type:</li> <li>Solder well single mating end single contact grouping</li> <li>Shell Material:</li> <li>Copper alloy</li> </ul>
<ul> <li>Radio Frequency Type Contact Characteristic Impedance In Ohms:</li> <li>50.0 single mating end single contact grouping</li> <li>Thread Size:</li> <li>0.438 inches</li> <li>Terminal Location:</li> <li>Back single mating end single contact grouping</li> <li>Contact Material:</li> <li>Copper alloy single mating end single contact grouping</li> <li>Contact Surface Treatment:</li> <li>Gold single mating end single contact grouping</li> <li>Insert Material:</li> <li>Plastic polytetrafluoroethylene single mating end</li> <li>Terminal Type:</li> <li>Solder well single mating end single contact grouping</li> <li>Shell Material:</li> <li>Copper alloy</li> <li>Shell Surface Treatment:</li> <li>Nickel</li> </ul>



Included Contact Type:

Coaxial pin single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material:** 

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0