

View Online at <https://aerobasegroup.com/nsn/5935-01-180-6651>

Thread Class:

2a

Thread Direction:

Right-hand

Overall Length:

1.867 inches

Mounting Hole Circle Radius:

1.093 inches

Overall Diameter:

2.188 inches

Environmental Protection:

Shock resistant and thermal shock resistant

Unthreaded Mounting Hole Diameter:

0.221 inches

Distance From Mounting Shoulder To Front Face:

1.555 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

9 number 16 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

12

Thread Size:

1.750 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Steel single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Glass single mating end

Contact Surface Treatment Specification:

Mil-g-45204, ty ii, class 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Steel comp 316l

Shell Material Specification:

Qq-s-763 federal specification single material response

Insert Material Specification:

Mil-p-19833 military specification single material response single mating end

Included Contact Quantity:

9 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.009 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Un

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.