## NSN 5935-01-181-1616

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-181-1616

Body Style:
Straight shape
Overall Length:
1.228 inches
Overall Height:
0.676 inches
Overall Width:
0.509 inches
Environmental Protection:
Corrosion resistant and humidity resistant and shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.115 inches and 0.125 inches
Distance Between Mounting Facility Centers:
0.989 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Removable single mating end single contact grouping
Shell Type:
Solid
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204 ty ii, grade c, cl 1 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Metal
Shell Surface Treatment:
Cadmium and chromate or zinc

## Insert Material Specification:

Mil-m-14 ty sdg-f or ty gpt-30f military specification 1st material response single mating end and mil-m-24519 ty get-30f military specification 2nd material response single mating end

## **Included Contact Quantity:**

15 single mating end single contact grouping

## NSN 5935-01-181-1616

Mil-std (military Standard):

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.009 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-24308 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-24308/4 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A039b0