NSN 5935-01-181-1618

Electrical Receptacle Connector - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5935-01-181-1618 |
|---|
| Body Style: |
| Straight shape, external coupling |
| Overall Length: |
| 1.060 inches |
| Overall Height: |
| 0.640 inches |
| Overall Width: |
| 0.640 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| Bnc single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Bayonet pin |
| Radio Frequency Type Contact Characteristic Impedance In Ohms: |
| 75.0 single mating end single contact grouping |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Contact Surface Treatment Specification: |
| Mil-g-45204 type 2, cl 2 military specification single treatment response single mating end single contact grouping |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Contact Material Specification: |
| Qq-c-530 federal specification single material response single mating end single contact grouping |
| Shell Material: |
| Copper alloy |
| Shell Material Specification: |
| Qq-b-626 federal specification single material response |
| Included Contact Quantity: |
| 1 single mating end single contact grouping |
| Included Contact Type: |

Special Features:

Solder flange mounted

Coaxial socket single mating end single contact grouping

NSN 5935-01-181-1618

Electrical Receptacle Connector - Page 2 of 2



| Precious Material And Location: |
|--|
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.005 gold grains, troy |
| Precious Material: |
| Gold |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |

Mil-std (military Standard):

Mil-g-45204 spec.